

Mostní odvodňovač podobrubníkový D400 - těžké dopravní zatížení



Kód	MK35CZ
Materiál	Litina
Hmotnost	58 kg
Norma	EN124-2
Balení	20 ks/pal
Třída zatížení	Vysoké dopravní zatížení

Mříž pro odvodnění mostů, 300x500, D400.

VÍKO:

- | Pant zajištěný čepem proti vyjmutí z rámu
- | Možnost uzamčení šroubem
- | Mříž rovná mezi žebry 35 mm
- | Nerozebíratelné spojení mříže s rámem
- | Velký vtokový průřez mříže 665 cm²

RÁM:

- | PUR tlumící vložka na rámu odolná vůči olejům a rozmrazovacím prostředkům
- | Proměnná výška osazení 85-165 mm

OSTATNÍ:

- | povrchová úprava černou práškovou barvou
- | Příčná rektifikace v rozsahu 0-40 mm,
- | Splňuje normu EN124-2

Warning: file_exists(): open_basedir restriction in effect.

File(/var/www/clients/client1/web105/web/media/product/image/4979.png) is not within the allowed path(s):

(/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media

in **/var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php** on line **272**

Warning: file_exists(): open_basedir restriction in effect. File(/var/www/clients/client1/web105/web/media/product/technical/4979.png) is not within the allowed path(s): (/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media



**MAX. ÚHEL
OTEVŘENÍ**



**ZAJIŠTĚNÍ PROTI
ODCIZENÍ**



**ODVOD
DEŠŤOVÝCH VOD**